



Data Sheet GS3200-08G

Product Appearance:



Key Features:

- **RJ45 Port:8*10/100/1000M(Auto MDI/MDIX)**
- AC In: 100V-240V 50HZ
- DC Out: 5V 1A(External power adapter)
- Bandwidth:1.6G full duplex
- Data Pin:12 36 45 78 Distance:100 Meters
- MAC Address:2K
- Agreement:IEEE802.3u,IEE 802.3x

Technical Specifications:

Standards	IEEE802.3 10Base-T IEEE802.3u 100Base-TX/FX	IEEE802.3x Flow control IEEE802.1p QoS IEEE802.1d Spanning Tree
Certifications	CCC, CE	
Ethernet Port	<ul style="list-style-type: none"> ➤ Connector: RJ45 ➤ Data Rate: 10/100/1000M ➤ Distance: 100m ➤ UTP Type: UTP-5E or higher level 	
Performance	<ul style="list-style-type: none"> ➤ Processing Type: Store and Forward ➤ Transmission Mode: half/full-duplex with auto-negotiation function ➤ MAC Table Size: 2K ➤ Buffer Space: 448K ➤ Back bandwidth: 1.6G ➤ Time Delay: < 150μs 	
Power	<ul style="list-style-type: none"> ➤ Power type: external power supply ➤ Input Voltage: AC100V ~ 240V 50/60Hz ➤ Connector: DC Socket ➤ Working Voltage: 5V ➤ Power Consumption: 1.8W ~ 4W 	
Environment	<ul style="list-style-type: none"> ➤ Storage Temperature: -40~70℃ ➤ Operating Temperature: -10~55℃ ➤ Relative Humidity: 5-90% (no condensation) 	
Warranty	1 year	
Physical Characteristics	<ul style="list-style-type: none"> ➤ Dimension: 140×52×28mm ➤ Weight: 0.30kg 	

➤ Color: Metal, Black

Solution Diagram:

