



Data Sheet HT400WTH-IP

HT400WTH-IP – 4Mega Pixel IP Camera

Product Appearance:



Highlights:

- **Outdoor Waterproof Camera ,**
- **1080P 3.0 MEGAPIXEL ,**
- **3.6mm fixed lens,**
- **40-45M IR,**
- **DC12V&POE (Optional),H.264**
- **Metal Housing**

Model NO.	HT400WTH-IP
Image Device	1/3" CMOS
Compression	H.264
TV System	PAL/NTSC
Total Pixels	4.0 Megapixel
Resolution	25fps@2MP (1920*1080)
WDR Range	Digital WDR
Exposure Mode	Auto/Iris Priority/Shutter Priority/Manual
Min. Illumination	0.01lux@(F1.6,AGC ON), 0 Lux with IR
S/N Ratio	>58db
Noise Reduction	2D/3D-DNR
Image Orientation	Mirror/Flip
Network	
Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
Remote Monitoring	IE Browsing, CMS 3 Control Software
ONVIF	Yes
Ethernet	100Mbps
POE	Optional
LENS	
Focal Length	3.6mm fixed Lens
OPERATIONAL(For OSD Model)	
Bit rate	32kbps-16Mbps
AGC	0-15
SENS-UP	OFF/Auto
Brightness	0-100
D-WDR	ON/OFF
Defog	ON/OFF
Backlight	ON/OFF

White Bal	ATW/Indoor/Outdoor
Day&Night	EXT/Color/B/W/Auto
IR Smart	Yes
2DNR/3DNR	Yes
Motion	4 area
Infrared LED	24pcs LEDs
IR Distance	40-45m
IR-CUT	YES
OPERATIONAL	
Operation Temperature	-35°C~60°C, 10%~90% Humidity
Water-proof Casing	IP66
ELECTRICAL	
Adapter Requirement	DC12V/POE (Optional)
MECHANICAL	
Color	White
Net Weight	530g/pcs

Solution Diagram:

